

## Product certificate K90948/02



K90948/01 Replaces

1 of 3 Page



# **PPSU press fittings**

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

## COMAP Benelux NV

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K536 E "Plastics piping systems of PE-X /Al intended for transport of hot and cold drinking water." dated 15-11-2011 inclusive amendment sheet dated 13-03-2018

Ronald Karel Kiwa



Kiwa Nederland B.V. Sir Winston Churchilllaan 273 Postbus 70 2280 AB RIJSWIJK The Netherlands Tel. +31 88 998 44 00 Fax +31 88 998 44 20 info@kiwa.nl

www.kiwa.nl

Publication of this certificate is allowed.

location

RGF

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid. This product certificate is only valid in combination with a Kiwa certified plastics piping system.

Company COMAP Benelux NV Alsembergsesteenweg 454 B-1653 DWORP België Tel. +32 (0)2 371 01 61 info@comap.be www.comap-group.com

Production Production location CARRO LUIGI SRL ZI du Curtillet Traversa Trecentottanta di Via 39170 PRATZ Lavoro e Industria, 20 25030 RUDIANO (BS) Italy

Production location PROVER SRL Via S. Pertini, 35/b 23807 MERATE (LC) Production location RASIM SRL Via Italo Calvino, 7 25018 MONTICHIARI (BS)

> **Certification process** consists of initial and regular assessment of:

- quality system
- product



page 2 of 3

### PPSU press fittings

#### **TECHNICAL SPECIFICATION**

#### Subject

PPSU press fittings

#### **Product characteristics**

The product complies to BRL K536-E Plastics piping systems of PE-X /Al intended for transport of hot and cold drinking water .

#### **Specification**

The fittings are suitable for the pipe dimensions as indicated in the table below.

Nominal outside	Wall thickness
Diameter	(mm)
(mm)	
16	2,0
20	2,0
26	3,0
32	3,0

Colour: Creme.

#### Fitness for contact with drinking water

This product is approved on the basis of the requirements for hygienic aspects set in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" ("Materials and chemicals in the supply of drinking water and warm tap water Regulation" dated 01-07-2017; published in the Government

Gazette).

These hygienic aspects are based on two main criteria. The product shall permanently comply with:

- The product recipe approved during the assessment procedure. This recipe is not to be changed without prior approval by Kiwa according to
  the Kiwa approval procedure for the hygienic aspects;
- Specific product requirements for the hygienic aspects.

The recipe and specific product requirements are laid down in the for confidentiality reasons undisclosed 'appendix hygienic aspects' to this certificate.

#### **MARKING**

#### **Fittings**

The minimum required marking on the fittings shall be:

- KIWA or on small products or or KK \* (if not possible KIWA only on the smallest packaging unit)\*\*;
- Kiwa (if not possible Kiwa only on the smallest packaging);
- the manufacturer's name, trade name or logo;
- nominal outside diameter of the corresponding pipe;
- production code.

Location of the marks: on every fitting.

The realization of the marks is as follows: clear, durable and indelible.

The smallest packaging unit of the fittings are provided with at least the following information:

- KIWA 🥞
- certificate number of the accompanying technical approval-with-product certificate of the piping system, according the marking of the belonging pipe;
- the manufacturer's name, trade name, system name or logo;
- material identification if the fitting body is made of plastics;
- nominal outside diameter and nominal wall thickness of the corresponding pipe in mm.

Location of the marks: on every package.

The realization of the marks is as follows: clear, durable and indelible on every packaging.

<sup>\*)</sup> for small fittings marking with only KK is permitted

<sup>\*\*)</sup> only after approval by Kiwa

page 3 of 3

## PPSU press fittings

#### Logistics

Production and assembly of the system is laid down in the annex of the certification agreement.

#### **APPLICATION AND USE**

The products are intended to be used for the transport of cold and hot drinking water with an operating temperature profile according to class 2 of ISO 10508 and an allowable working pressure of maximum 10 bar.

#### **RECOMMENDATIONS FOR CUSTOMERS**

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

COMAP Benelux NV

and, if necessary,

Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.